



KCDE – 200



ALL HYDRAULIC SKID MOUNTED CORE DRILLING MACHINE

**Core Drilling , Augering & DTH Drilling Capabilities
Skid Mounted , Fast and Easy Assembly , Light Weight
Reliable and Stable with Low Maintenance Cost**

KCDE 200 TECHNICAL DATA

ENGINE

Diesel Engine
27 HP @ 3400 rpm , Twin Cylinder
Air cooled , Electric Start

DRILL MAST

Robust Frame
Max. Rod length Handling Capacity 3.0 m
Mast Raising and Lowering with Hydraulic Cylinder and Locking pins for Angular Drilling

FEED SYSTEM

Chain Sprocket Feed System
For 3 m rod pull
Max. Pull – Up Force : 2500 Kg
Max. Pull – Down Force : 2500 Kg
Max. Pull – Up Speed : 25 M/min
Chain Feed System driven by hydraulic motors with variable micro control of feed
During drilling and fast feed during rod handling

ROTATION HEAD

Hollow Spindle Direct Drive , Single Hydraulic Motor With Gear Transmission
Maximum Torque 240 Nm @ 500 rpm
Water / Air water swivel
Rotation head lateral Swivel movement

HYDRAULICS

High Quality Hydraulic Gear Pump
Hydraulic Tank Capacity 100 Liters
Complete Range of Parker/Gates Hydraulic Hoses
Sauer Danfoss PVG32 Load Sensing Control Valves and Hydraulic Motors

WIRELINE WINCH

Hydraulically operated Wireline Winch along with 350 meters wire rope.

DRILLING DEPTH CAPACITIES

Diamond Core Drilling
100m H Wireline Drill Rod
200 m N Wireline Drill Rod
240 m B Wireline Drill Rod

The manufacturer reserves the right to change design and make modifications



KUVAWALA CORE DRILL EQPT. PVT. LTD.

524 , Arun Chambers , Tardeo , Mumbai 400 034. INDIA

TEL : +91 22 66635452 / +91 22 23516141 FAX : +91 22 66607358

E-MAIL : hmk@kuvawalacoredrill.com , info@kuvawalacoredrill.com

www.kuvawalacoredrill.com