



X SERIES CASINGS



SIZE	LENGTH	O.D.	I.D.	T.P.I	WEIGHT KGS	PART NUMBERS
AX	0.5	57.4	50.8	8	3	K8-01-001
AX	1	57.4	50.8	8	5.2	K8-01-002
AX	1.5	57.4	50.8	8	7.5	K8-01-003
AX	3	57.4	50.8	8	14.8	K8-01-004
BX	0.5	73	65	8	5.1	K8-02-001
BX	1	73	65	8	9.6	K8-02-002
BX	1.5	73	65	8	11.4	K8-02-003
BX	3	73	65	8	21.8	K8-02-004
NX	0.5	88.9	80.9	8	5.7	K8-03-001
NX	1	88.9	80.9	8	9.8	K8-03-002
NX	1.5	88.9	80.9	8	14	K8-03-003
NX	3	88.9	80.9	8	26.6	K8-03-004
HX	0.5	114.3	104.6	5	8.3	K8-04-001
HX	1	114.3	104.6	5	14.9	K8-04-002
HX	1.5	114.3	104.6	5	21.5	K8-04-003
HX	3	114.3	104.6	5	41.3	K8-04-004

ALL KUVAWALA CASINGS ARE MANUFACTURED FROM THE HIGHEST QUALITY RAW MATERIALS i.e. COLD DRAWN SEAMLESS TUBES OF GRADE SAE 1541 THAT ARE IMPORTED . THESE HAVE EXTREMELY HIGH MECHANICAL PROPERTIES AND STRAIGHTNESS BETTER THAN 1 : 2000 . ALL DRILL CASINGS ARE PARALLEL WALL

STANDARD ' X ' SERIES CASINGS ARE FLUSH COUPLED AND A COUPLING IS SUPPLIED WITH EACH CASING LENGTH. COUPLINGS ARE MADE OF HEAT TREATED ALLOY STEEL.

WEIGHTS GIVEN ABOVE ARE INCLUSIVE OF COUPLING WEIGHT.