



W SERIES DRILL RODS



SIZE	LENGTH	O.D.	I.D.	T.P.I	WEIGHT KGS	PART NUMBERS
AW	0.5	43.75	31.4	3	3.7	K7-01-001
AW	1	43.75	31.4	3	6.6	K7-01-002
AW	1.5	43.75	31.4	3	9.6	K7-01-003
AW	3	43.75	31.4	3	18.4	K7-01-004
BW	0.5	54	38	3	6.0	K7-02-001
BW	1	54	38	3	10.6	K7-02-002
BW	1.5	54	38	3	15.1	K7-02-003
BW	3	54	38	3	28.7	K7-02-004
NW	0.5	66.7	51	3	7.6	K7-03-001
NW	1	66.7	51	3	13.3	K7-03-002
NW	1.5	66.7	51	3	19.0	K7-03-003
NW	3	66.7	51	3	36.0	K7-03-004
HW	0.5	88.9	71.5	3	11.2	K7-04-001
HW	1	88.9	71.5	3	19.9	K7-04-002
HW	1.5	88.9	71.5	3	28.5	K7-04-003
HW	3	88.9	71.5	3	54.6	K7-04-004

ALL KUVAWALA DRILL RODS ARE MANUFACTURED FROM THE HIGHEST QUALITY RAW MATERIALS i.e. COLD DRAWN SEAMLESS TUBES OF GRADE SAE 1541 . THESE HAVE EXTREMELY HIGH MECHANICAL PROPERTIES AND STRAIGHTNESS BETTER THAN 1 : 4000 . ALL DRILL RODS ARE PARALLEL WALL.

STANDARD ' W ' SERIES DRILL RODS ARE FLUSH COUPLED AND A COUPLING IS SUPPLIED WITH EACH ROD LENGTH. COUPLINGS ARE MADE OF 4140 ALLOY STEEL.

WEIGHTS GIVEN ABOVE ARE INCLUSIVE OF COUPLING WEIGHT.